



CONSTRUCTION
CONCEPTS
INTERNATIONAL

www.ccinetwork.com
P.O. Box 68 • Morristown, AZ 85342
p 800.677.3933 • f 800.684.0788
sales@ccinetwork.com

Outstanding Combination Rebar Bender & Cutter Units.

DIAMOND®

DBC-2520
DBC-2525
Combo Units



Maintaining the rebar cutter is easy, it's simply removed by unbolting the wing nuts & washers on the two heavy duty threaded U-bolts with sleeves.

"These combo units are protected by a GFI plug"

This is an essential combination rebar cutter and bender. It simply combines the very popular DBD-25X bender and the DC-20WH or DC-25X rebar cutter both together on a stationary stand. The important advantage to owning this versatile combination unit is that the rebar cutter can be simply removed and used in any portable application or locked into a stationary position and then operated by the foot pedal switch. The other advantage is production, the bender table is at the ideal working height and cutter can be used independently from the rebar bender. The DBD-25X bends rebar from 0 -180 degrees and has two optional rollers for bending circular patterns. The BCSE-25X stand joins the rebar bender & cutter together (some assembly required). One year parts and labor warranty included.

Specifications for DBC-2520 & DBC-2525 Combination Units

Models #'s	DBC-2520	DBC-2525
Max. Cutting	#6 or ¾" Grade 60	#8 or 1" Grade 60
Max. Bending	#7 or 7/8" Grade 60	#7 or 7/8" Grade 60
Cutter Power	115 Volt 50/60 Hz -10 amps	115 Volt 50/60 Hz -12 amps
Bender Power	115 Volt 50/60 Hz -12 amps	115 Volt 50/60 Hz -12 amps
Total Weight (kg)	250 lbs. (113.5)	274 lbs. (124.5)
Dimensions (mm)	19.25" (490) L x 24.75" (629) W x 37.25 (946) H	

"Our Tools make you Money"