



**CONSTRUCTION  
CONCEPTS  
INTERNATIONAL**

www.ccinetwork.com  
P.O. Box 68 • Morristown, AZ 85342  
p 800.677.3933 • f 800.684.0788  
sales@ccinetwork.com

## Outstanding Combination Rebar Bender & Cutter Units.

**DIAMOND®**

DBC-3225  
DBC-3232  
Combo Units

Maintaining the rebar cutter is easy, it's simply removed by unbolting the wing nuts & washers on the two heavy duty threaded U-bolts with sleeves.



***"Standard foot pedal control switch is not shown"***

This is an essential combination rebar cutter and bender. It simply combines the DBD-32X bender and the DC-25X or DC-32X rebar cutter both together on a stationary stand. The important advantage to owning this combination unit is that the rebar cutter can be simply removed and used in a portable application or locked into a stationary position and then operated by the foot pedal switch. The other advantage is production, the bender table is at the ideal working height and cutter can be used independently from the rebar bender. The DBD-32X bends rebar from 0 -180 degrees. This combination unit is made up of three components; the bender, the cutter, and the BCSE-32X combination stand with electrical outlet (some assembly required). One year parts and labor warranty.

### Specifications for DBC-3225 & DBC-3232 Combination Units

Models #'s	DBC-3225	DBC-3232
Max. Cutting	#8 or 1" Grade 60	#10 or 1-1/4" Grade 60
Max. Bending	#9 or 1-1/8" Grade 60	#9 or 1-1/8" Grade 60
Cutter Power	115 Volt 50/60 Hz -12 amps	115 Volt 50/60 Hz -18 amps
Bender Power	115 Volt 50/60 Hz -12 amps	115 Volt 50/60 Hz -12 amps
Total Weight (kg)	482 lbs. (219)	511 lbs. (232)
Dimensions (mm)	23" (590) L x 27" (686) W x 37.25 (946) H	

**"Our Tools make you Money"**