

# Husqvarna K 4000

This electric all-round cutter minimises the amount of water and slurry. Unlike other electric cutters, the blade rotates forward, cutting into the material efficiently with minimum effort on the operator. K 4000 is easily adaptable for dry cutting with the Vac attachment accessory for minimal dust generation.

✿ Cutting depth, **5 in**

max

✿ Blade **14 in**

diameter, max

**\$999.00**

Excl Tax

Article number :

POWER CUTTER K 4000 120 V | NA - 967 08 40-01

NEW



## FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



### Constant-flow water valve

The integrated regulator controls the water volume, ensuring a constant flow to the blade. It also ensures the amount of water is sufficient to bind the dust without creating an excess of water.



### Ergonomically designed rear handle

Power cord inlet located underneath the handle enables ease of use and comfortable handling with hassle free operation.

### Increased productivity

The new pop-up carbon brushes protects the collector from unforeseen rotor changes which increases reliability and enables longer service intervals.



### Easy serviceability

The one-piece inspection lid and Torx screws make it easy to assemble and service.



- Simple blade change
- "Pulling" rotation
- Generously dimensioned miter gear
- Overload protection
- Perfect for indoor use
- Elgard™
- Electronic Softstart™
- Adjustment to openings

- Blocks, curbstones and pavers
- Cast concrete
- Deep cutting
- Floors and walls
- Grooves
- Pipe trenches
- Pipes

## SPECIFICATIONS

### Engine

Rated input power	<b>2.4 hp</b>
Voltage	<b>100-120 V</b>
Frequency	<b>50-60 Hz</b>

### Dimensions

Product size width	<b>8.7 in</b>
Product size height	<b>12.3 in</b>
Weight	<b>16.8 lbs</b>

### Vibrations

Vibrations left/front handle	<b>3.5 m/s<sup>2</sup></b>
Vibrations right/rear handle	<b>3.5 m/s<sup>2</sup></b>

### Cutting equipment

Cutting depth, max	<b>5 in</b>
Blade diameter, max	<b>14 in</b>
Arbor diameter	<b>1 in</b>
Blade thickness, max	<b>0.22 in</b>
Peripheral speed, max	<b>19690 fpm</b>

### Sound and noise

Sound power level, guaranteed (LWA)	<b>105 dB(A)</b>
Sound pressure level at operators ear	<b>95 dB(A)</b>