

# Husqvarna K 770

The Husqvarna K 770 is a powerful all-round power cutter with features that make it one of the best power cutters on the market. Equipped with semi-automatic SmartTension™ system allows for optimal power transmission, minimum wear and maximum belt life. The light weight, outstanding power-to-weight ratio, the reliable start and exceptionally low vibrations mean less strain and maximized productivity. Suitable for road work and easy to cut in a straight or curved track or close to sidewalk when used with KV7 trolley.

- ✿ Cutting depth, **5 in**  
max
- ✿ Blade **14 in**  
diameter, max
- Output power **5 hp**

**\$1,170.00**

Excl Tax

Article number :

POWER CUTTER K 770 14" | 1" / 20mm - 967 68 21-01



## FEATURES

Want to take a closer look? Learn more about the product in depth by exploring its features and benefits.



### Easy and optimal belt tensioning

The semi-automatic SmartTension minimises the risk of under- and over tensioning



### Light and powerful

A light, compact and powerful machine with superior power-to-weight ratio.

### Heavy-duty cutting arm

The new-designed cast magnesium crankcase has a three-bolt joint to attach the cutting head, enabling higher torsional rigidity than the previous two-bolt solution.



### Long service intervals

A strong Poly-V belt combined with our maintenance-free DuraStarter™ and efficient filter-system Active Air Filtration™ ensure long service intervals.



- Digital ignition with optimised timing
- Exceptionally low vibrations
- Easy to start
- Maintenance-free air filter
- High power with less fuel
- Optimized engine performance
- Less slurry and low water consumption
- Easy to change blade guard position
- Fits multiple blade bushings
- Less emissions and fuel consumption
- Blade retarder
- Maintenance-free starter
- Reduced wear
- Cuts close to walls or ground
- Active Air Filtration™

- Anti-vibration system
- DuraStarter™
- EasyStart
- Poly-V belt
- SmartCarb™
- Adjustment to openings
- Asphalt
- Blocks, curbstones and pavers
- Burying of cables
- Cast concrete
- Floors and walls
- Rails
- Rescue cutting
- Blade Shaft And Bearings

## SPECIFICATIONS

### Engine

Output power	<b>5 hp</b>
Cylinder displacement	<b>4.48 cu.inch</b>
Electrode gap	<b>0.02 in</b>

### Dimensions

Product size width	<b>8.86 in</b>
Product size height	<b>16.34 in</b>
Weight	<b>22.4 lbs</b>

### Vibrations

Vibrations left/front handle	<b>2.0 m/s<sup>2</sup></b>
Vibrations right/rear handle	<b>2.3 m/s<sup>2</sup></b>

### Cutting equipment

Cutting depth, max	<b>5 in</b>
Blade diameter, max	<b>14 in</b>
Arbor diameter	<b>0.8/1 in</b>
Blade thickness, max	<b>0.2 in</b>
Peripheral speed, max	<b>18000 fpm</b>

### Sound and noise

Sound power level, guaranteed (LWA)	<b>115 dB(A)</b>
Sound pressure level at operators ear	<b>101 dB(A)</b>

### Certifications

Cert machine dir. 2006/42/EC Decl. No.	<b>EURO TEST CERTIFICATE SEC/10/2285</b>
--	--